

Safety Data Sheet Renoil 130-W to 500-W White Oils

SDS Revision Date: 3/24/2015

1. Identification of the substance/mixture and of the company

1.1. Product identifier

Product Identity Renoil 130-W, Renoil 150-W, Renoil 180-W,

Renoil 200-W, Renoil 220-W, Renoil 350-W, Renoil 380-W, Renoil 485-W, Renoil 500-W

Alternate Names White mineral oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Lubricant, personal care, food & plastics process oil

Application Method Varied

1.3. Details of the supplier of the safety data sheet

Company Name Renkert Oil

3817 Main Street

Morgantown, PA 19543

Emergency

CHEMTREC (USA) (800) 424-9300 **24 hour Emergency Telephone No.** or 1 703 527 3887

Customer Service: Renkert Oil Product Information: +1 (610) 286-8012

Email: orders@renkertoil.com SDS Info:mproudfoot@renkertoil.com

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Hazards: none known

2.2. Label elements

No known significant effects or critical hazards

No Signal word

[Prevention]: [Response]:

[Storage]: [Disposal]:

No GHS prevention statements

[Storage]:

No GHS storage statements

No GHS response statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|---------------------------|-------|
| White mineral oil CAS Number: 8042-47-5 | 100 | none | |

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Immediately flush the eyes with large amounts of water for at least 15 minutes, alternately

lifting the upper and lower eyelids. After 5 minutes, if appropriate, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Not expected to cause prolonged or

significant eye irritation.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser. Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response.

Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion Not expected to be harmful if swallowed. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview No known significant effects or critical hazards.

5. Fire-fighting measures

NFPA 704 Hazard Class Health: 0 Flammability: 1 Instability: 0



0 (Minimal) 1 (Slight) 0 (Minimal) 1 (Slight) 2 (Moderate) 3 (Serious)

4 (Severe)

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide and unidentified organic compounds will be evolved when this material undergoes combustion

5.3. Advice for fire-fighters

Firefighting personnel should respond with appropriate protective clothing, firefighting gear, and breathing equipment as trained. All other personnel should exit the area and proceed to a gathering point in an area unaffected by the fire and smoke.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities as appropriate or required.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from flames and hot surfaces. Use good personal hygiene practices and wear appropriate personal protective equipment. Spills will produce very slippery surfaces.

7.2. Conditions for safe storage, including any incompatibilities

Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Incompatible materials: Strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|-----------|-------------------|--------|--|
| 8042-47-5 | White Mineral Oil | OSHA | exposure limits for oil mist are 5 mg/m3 |
| | | ACGIH | 5 mg/m3 |
| | | NIOSH | No Established Limit |

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

Carcinogen Data

| CAS No. | Ingredient | Source | Value | | |
|-----------|-------------------|--------|--------------------------|--|--|
| 8042-47-5 | White Mineral Oil | OSHA | Select Carcinogen: No | | |
| | | NTP | Known: No; Suspected: No | | |

8.2.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Wear overalls to keep skin contact to a minimum. Nitrile rubber gloves should be worn.

Engineering Provide adequate ventilation. Where reasonably practicable this should be achieved by the **Controls** use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, smoking or **Practices** using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Practices using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

9. Physical and chemical properties

Appearance Colorless Liquid
Odor Petroleum Odor
Odor threshold Not Measured
pH Not Applicable
Melting point / freezing point Not Applicable
Initial boiling point and boiling range > 260 C (500 F)

Flash Point 350 F (177 C) minimum (Cleveland Open Cup)

Evaporation rate (Ether = 1) Not Measured Flammability (solid, gas) Not Applicable

Upper Explosive Limit: Not Measured

Vapor pressure (Pa) < 0.01 mmHg @ 37.8 C (100 F)

Vapor Density > 1

Specific Gravity 0.85 - 0.88 @ 15.6 C (60.1F) / 15.6 C (60.1 F)

Solubility in Water Soluble in hydrocarbon solvents, insoluble in water.

Partition coefficient n-octanol/water (Log Kow) Not Measured
Auto-ignition temperature

Not Measured

Decomposition temperature

Not Measured

Viscosity (cSt) 25-120 cSt @ 40 C (104 F)

Pour point -12C (10 F)

DMSO extract by IP346: Less than 3.0 wt %

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

None known (none expected).

10.4. Conditions to avoid

Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.

10.5. Incompatible materials

Strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.6. Hazardous decomposition products

Not anticipated under conditions of normal use.

11. Toxicological information

Acute toxicity

| Ingredient | Oral LD50, g/kg | Skin LD50, g/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, g/L/4hr | Inhalation Gas LD50, ppm |
|-------------------------------|----------------------------|--------------------------|--|---|-----------------------------------|
| White Mineral Oil (8042-47-5) | >5 Rat - Category: 5 | >2g/kg Category: 4 | No data available | >5 Rat - Category: 5 | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity

acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description | | |
|-------------------------------|----------|---------------------------|--|--|
| Acute toxicity (oral) | | Not Applicable | | |
| Acute toxicity (dermal) | | Not Applicable | | |
| Acute toxicity (inhalation) | | Not Applicable | | |
| Skin corrosion/irritation | | Not Applicable | | |
| Serious eye damage/irritation | | Not Applicable | | |
| Respiratory sensitization | | Not Applicable | | |
| Skin sensitization | | Not Applicable | | |
| Germ cell mutagenicity | | Not Applicable | | |
| Carcinogenicity | | Not Applicable | | |
| Reproductive toxicity | | Not Applicable | | |
| STOT-single exposure | | Not Applicable | | |
| STOT-repeated exposure | | Not Applicable | | |
| Aspiration hazard | | Not Applicable | | |

12. Ecological information

GHS Classification: No classified hazards

12.1. Toxicity ECOTOXICITY

All acute aquatic toxicity studies on samples of similar oils show acute toxicity values greater than 100mg/l for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with predicted aquatic toxicity of these substances based on their hydrocarbon compositions. Not classified hazards.

ENVIRONMENTAL FATE This material is considered inherently biodegradable. This material is not expected to present any environmental problems other than those associated with oil spills. This material is not readily biodegradable. See Section 6 for Accidental Release Measures.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|-------------------------------|--------------------------|----------------------------------|-------------------------|
| White Mineral Oil (8042-47-5) | 5,000, Oncorhynchus | 1,000, Daphnia | Not |
| | mykiss | magna | Available |

12.2. Persistence and degradability

Persistence per IOPC Fund definition: persistent

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment (persistant, bioaccumulative and toxic, very persistent, very bioaccumulative) This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

None expected

13. Disposal considerations

13.1. Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (See B.C. Reg. GY/92 Waste Management Act;

consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (See B.C. Reg. GY/92 Waste Management Act; R.R.O. 1990, Reg. 347 General-Waste Management; C.C.SM.c. W40 The Waste Reduction and Prevention Act; N.S. Reg. 51/95 and N.S. Reg. 179/96 for examples of Provincial legislation.)

14. Transport information

DOT (Domestic IMO / IMDG ICAO/IATA

Surface (Ocean

Transportation) Transportation)

14.1. UN Not Applicable

number

14.2. UN PETROLEUM OIL, Not Not

proper N.O.I.B.N., NOT Regulated Regulated **shipping** REGULATED AS A

name HAZARDOUS MATERIAL

14.3. DOT Hazard IMDG: Not Air

Transport Class: Not Applicable Applicable Class: Not hazard DOT Label: --- Sub Applicable

class(es) Class: Not Applicable

14.4. Not Applicable Not Not

Packing Applicable Applicable

group

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented.

Toxic Substance Control All components of this material are either listed or exempt from listing on the

Act (TSCA) TSCA Inventory.

WHMIS Classification Not Regulated

US EPA Tier II Hazards Fire: No Reactive: No

Sudden Release of Pressure: No

Delayed (Chronic): No Immediate (Acute):No

EPCRA 311/312 Chemicals and RQs: (No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous: (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals: (No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

N.J. RTK Substances (>1%): (No Product Ingredients Listed)

Penn RTK Substances (>1%): (No Product Ingredients Listed)

National Chemical Inventories

Chemical name AICS DSL CHINA EINCS ENCS KOREA PICCS TSCA CANADA

Distillates (petroleum), hydrotreated X X X X X X X X X X X X X X X A heavy paraffinic - (64742-54-7)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

The data on this SDS relates only to the specific material described and does not relate to its use in combination with other materials or in any process

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

End of Document